



PRODUCT DATA SHEET

DIEDRESS - 140

(Talcum Sodium Silicate base diecoat For GDC & LPDC)

PRODUCT :

Diedress – 140 is an insulating coating used to protect the accurately machined die and core faces, to control solidification, to give best possible surface finish and to ease die operation

FUNCTION :

In GDC and LPDC, castings are produced with larger / thinner sectioned aluminium alloys.

When hot metal (aluminium alloy at 720°C) is cast into die (at 250°C) the rate of heat extraction from the metal will be high and as a consequence fluidity of the cast metal will be reduced. Correct use of an insulating coating can control the rate of heat extraction in various parts of the die and so retain fluidity as well as provides a desirable directional solidification pattern in the casting

ADVANTAGES:

- 1) Easy release of castings.
- 2) Easy filling of die-cavity.
- 3) Better surface finish of castings.
- 4) Economical

APPLICATION :

Dilute the coating with soft water in the ratio 1:3(Product : Water) mix uniformly and apply coating by spraying. The application of the coating is varies from very thin, where maximum chilling is required and thick on runners, feeders, thin cast sections, etc.

Spray the diluted coating on to the die and core faces using a good atomizing gun. The die temperature should be between 120 and 200°C so that the spray hits and dries quickly without running. Then re-heat the die to normal working temperature before casting metal.

CERAFLUX INDIA PVT. LTD.

F-59 & 60, M.I.D.C. Gokul Shirgaon, Kolhapur – 416234, Maharashtra (India)
Phone: +91 8380099227 | Email: marketing@ceraflux.com
www.ceraflux.com



PRODUCT DATA SHEET

PHYSICAL PROPERTIES:

1 COLOUR:	Off-White
2 APPEARANCE:	Paste
3 SECIFIC GRAVITY @ 27±3°C:	1.58 – 1.68

STANDARD PACKING:- 8 / 40 K.g P.C

NOTE : -Above information is true & accurate based on controlled laboratory testing ,however user is responsible for determining suitability for application at their end, no guarantee is implied since the conditions in actual use differ widely & beyond our control.

CERAFLUX INDIA PVT. LTD.

F-59 & 60, M.I.D.C. Gokul Shirgaon, Kolhapur – 416234, Maharashtra (India)
Phone: +91 8380099227 | Email: marketing@ceraflux.com
www.ceraflux.com